


NPTF MALE 60° FLARE

**MASCHIO NPTF SVASATURA
60°**

AGN

part nr. codice	hose ID		size	thread T	d		hex E			cut-off C	
	[in]	[mm]			[in]	[mm]	[in]	[mm]	key	[in]	[mm]
SP02020410	1/4	6,4	4	1/8-27	0,16	4,0	0,47	12	1/2"	0,87	22
SP02020413	1/4	6,4	4	1/4-18	0,16	4,0	0,59	15	5/8"	1,10	28
SP02020417	1/4	6,4	4	3/8-18	0,16	4,0	0,75	19	3/4"	1,10	28
SP02020513	5/16	8	5	1/4-18	0,22	5,5	0,59	15	5/8"	1,10	28
SP02020517	5/16	8	5	3/8-18	0,22	5,5	0,75	19	3/4"	1,10	28
SP02020613	3/8	9,5	6	1/4-18	0,28	7,0	0,59	15	5/8"	1,10	28
SP02020617	3/8	9,5	6	3/8-18	0,28	7,0	0,75	19	3/4"	1,10	28
SP02020621	3/8	9,5	6	1/2-14	0,28	7,0	0,87	22	7/8"	1,34	34
SP02020817	1/2	12,7	8	3/8-18	0,37	9,5	0,75	19	3/4"	1,14	29
SP02020821	1/2	12,7	8	1/2-14	0,37	9,5	0,87	22	7/8"	1,38	35
SP02021021	5/8	16	10	1/2-14	0,47	12,0	0,87	22	7/8"	1,38	35
SP02021027	5/8	16	10	3/4-14	0,47	12,0	1,06	27	1.1/16"	1,42	36
SP02021227	3/4	19	12	3/4-14	0,59	15,0	1,06	27	1.1/16"	1,46	37
SP02021233	3/4	19	12	1-11.1/2	0,59	15,0	1,42	36	1.7/16"	1,69	43
SP02021633	1	25,4	16	1-11.1/2	0,79	20,0	1,42	36	1.7/16"	1,73	44
SP02021642	1	25,4	16	1.1/4- 11.1/2	0,79	20,0	1,81	46	1.13/16"	1,81	46



**NPSM FEMALE 60° FLARE
WITH CRIMPED NUT**

**FEMMINA NPSM SVASATURA
60° CON DADO PINZATO**

DKNPSM

part nr. codice	hose ID		size	thread T	d		hex E			cut-off C	
	[in]	[mm]			[in]	[mm]	[in]	[mm]	key	[in]	[mm]
SP16310413	1/4	6,4	4	NPSM 1/4-18	0,16	4,0	0,75	19	3/4"	0,71	18
SP16310617	3/8	9,5	6	NPSM 3/8-18	0,28	7,0	0,87	22	7/8"	0,79	20
SP16310821	1/2	12,7	8	NPSM 1/2-14	0,37	9,5	1,06	27	1.1/16"	0,91	23