


JIC MALE 37° FLARE

MASCHIO JIC SVASATURA 37°




AGJ

part nr. codice	hose ID			thread		d		hex E		cut-off C	
	[in]	[mm]	size	T	[in]	[mm]	[in]	[mm]	key	[in]	[mm]
SP02550411	1/4	6,4	4	7/16-20	0,16	4,0	0,47	12	1/2"	1,06	27
SP02550412	1/4	6,4	4	1/2-20	0,16	4,0	0,55	14	9/16"	1,06	27
SP02550414	1/4	6,4	4	9/16-18	0,16	4,0	0,59	15	5/8"	1,06	27
SP02550514	5/16	8	5	9/16-18	0,22	5,5	0,59	15	5/8"	1,06	27
SP02550614	3/8	9,5	6	9/16-18	0,28	7,0	0,59	15	5/8"	1,06	27
SP02550619	3/8	9,5	6	3/4-16	0,28	7,0	0,75	19	3/4"	1,18	30
SP02550622	3/8	9,5	6	7/8-14	0,28	7,0	0,94	24	15/16"	1,34	34
SP02550819	1/2	12,7	8	3/4-16	0,37	9,5	0,75	19	3/4"	1,22	31
SP02550822	1/2	12,7	8	7/8-14	0,37	9,5	0,94	24	15/16"	1,38	35
SP02550827	1/2	12,7	8	1.1/16-12	0,37	9,5	1,06	27	1.1/16"	1,46	37
SP02551022	5/8	16	10	7/8-14	0,47	12,0	0,94	24	15/16"	1,38	35
SP02551027	5/8	16	10	1.1/16-12	0,47	12,0	1,06	27	1.1/16"	1,46	37
SP02551222	3/4	19	12	7/8-14	0,59	15,0	0,94	24	15/16"	1,42	36
SP02551227	3/4	19	12	1.1/16-12	0,59	15,0	1,06	27	1.1/16"	1,50	38
SP02551230	3/4	19	12	1.3/16-12	0,59	15,0	1,26	32	1.1/4"	1,62	41
SP02551233	3/4	19	12	1.5/16-12	0,59	15,0	1,34	34	M	1,65	42
SP02551627	1	25,4	16	1.1/16-12	0,79	20,0	1,06	27	1.1/16"	1,54	39
SP02551633	1	25,4	16	1.5/16-12	0,79	20,0	1,34	34	M	1,69	43
SP02551641	1	25,4	16	1.5/8-12	0,79	20,0	1,65	42	M	1,81	46

JIC FEMALE 37° FLARE WITH
HEXAGON AND CRIMPED NUT

FEMMINA JIC SVASATURA 37° CON
ESAGONO E DADO PINZATO




DKJ-HE

part nr. codice	hose ID			thread T	d		hex E			hex E1			cut-off C	
	[in]	[mm]	size		[in]	[mm]	[in]	[mm]	key	[in]	[mm]	key	[in]	[mm]
SP16260411	1/4	6,4	4	7/16-20	0,16	4,0	0,59	15	5/8"	0,47	12	1/2"	0,64	16,3
SP16260412	1/4	6,4	4	1/2-20	0,16	4,0	0,67	17	11/16"	0,47	12	1/2"	0,79	20
SP16260414	1/4	6,4	4	9/16-18	0,16	4,0	0,75	19	3/4"	0,67	17	11/16"	0,85	21,5
SP16260514	5/16	8	5	9/16-18	0,22	5,5	0,75	19	3/4"	0,67	17	11/16"	0,85	21,5
SP16260619	3/8	9,5	6	3/4-16	0,28	7,0	0,95	24	15/16"	0,75	19	3/4"	0,91	23
SP16260819	1/2	12,7	8	3/4-16	0,37	9,5	0,95	24	15/16"	0,87	22	7/8"	0,99	25
SP16260822	1/2	12,7	8	7/8-14	0,37	9,5	1,06	27	1.1/16"	0,87	22	7/8"	1,06	27
SP16261022	5/8	16	10	7/8-14	0,47	12,0	1,06	27	1.1/16"	0,95	24	15/16"	1,06	27
SP16261227	3/4	19	12	1.1/16-12	0,59	15,0	1,26	32	1.1/4"	1,06	27	1.1/16"	1,12	28,5
SP16261633	1	25,4	16	1.5/16-12	0,79	20,0	1,50	38	1.1/2"	1,26	32	1.1/4"	1,26	32

**JIC FEMALE 37° FLARE WITH
CRIMPED NUT**

**FEMMINA JIC SVASATURA 37° CON DADO
PINZATO**




DKJ

part nr. codice	hose ID			thread		d		hex E		cut-off C	
	[in]	[mm]	size	T	[in]	[mm]	[in]	[mm]	key	[in]	[mm]
SP16250411	1/4	6,4	4	7/16-20	0,16	4,0	0,59	15	5/8"	0,51	13
SP16250412	1/4	6,4	4	1/2-20	0,16	4,0	0,67	17	11/16"	0,59	15
SP16250414	1/4	6,4	4	9/16-18	0,16	4,0	0,75	19	3/4"	0,63	16
SP16250512	5/16	8	5	1/2-20	0,22	5,5	0,67	17	11/16"	0,59	15
SP16250514	5/16	8	5	9/16-18	0,22	5,5	0,75	19	3/4"	0,63	16
SP16250614	3/8	9,5	6	9/16-18	0,28	7,0	0,75	19	3/4"	0,63	16
SP16250619	3/8	9,5	6	3/4-16	0,28	7,0	0,95	24	15/16"	0,63	16
SP16250819	1/2	12,7	8	3/4-16	0,37	9,5	0,95	24	15/16"	0,67	17
SP16250822	1/2	12,7	8	7/8-14	0,37	9,5	1,06	27	1.1/16"	0,75	19
SP16250827	1/2	12,7	8	1.1/16-12	0,37	9,5	1,26	32	1.1/4"	0,75	19
SP16251022	5/8	16	10	7/8-14	0,47	12,0	1,06	27	1.1/16"	0,75	19
SP16251027	5/8	16	10	1.1/16-12	0,47	12,0	1,26	32	1.1/4"	0,75	19
SP16251227	3/4	19	12	1.1/16-12	0,59	15,0	1,26	32	1.1/4"	0,79	20
SP16251230	3/4	19	12	1.3/16-12	0,59	15,0	1,42	36	1.7/16"	0,83	21
SP16251233	3/4	19	12	1.5/16-12	0,59	15,0	1,50	38	1.1/2"	0,83	21
SP16251633	1	25,4	16	1.5/16-12	0,79	20,0	1,50	38	1.1/2"	0,87	22

**JIC 45° FEMALE 37° FLARE
WITH CRIMPED NUT**

**FEMMINA JIC 45° SVASATURA 37°
CON DADO PINZATO**




DKJ-45

part nr. codice	hose ID			thread T	d		hex E			cut-off C		drop H	
	[in]	[mm]	size		[in]	[mm]	[in]	[mm]	key	[in]	[mm]	[in]	[mm]
SP28250411	1/4	6,4	4	7/16-20	0,16	4,0	0,59	15	5/8"	1,34	34,0	0,51	13,0
SP28250412	1/4	6,4	4	1/2-20	0,16	4,0	0,67	17	11/16"	1,57	40,0	0,51	13,0
SP28250414	1/4	6,4	4	9/16-18	0,16	4,0	0,75	19	3/4"	1,57	40,0	0,59	15,0
SP28250514	5/16	8	5	9/16-18	0,22	5,5	0,75	19	3/4"	1,85	47,0	0,63	16,0
SP28250614	3/8	9,5	6	9/16-18	0,28	7,0	0,75	19	3/4"	1,93	49,0	0,63	16,0
SP28250619	3/8	9,5	6	3/4-16	0,28	7,0	0,95	24	15/16"	2,00	51,0	0,71	18,0
SP28250819	1/2	12,7	8	3/4-16	0,37	9,5	0,95	24	15/16"	2,36	60,0	0,75	19,0
SP28250822	1/2	12,7	8	7/8-14	0,37	9,5	1,06	27	1.1/16"	2,48	63,0	0,79	20,0
SP28250827	1/2	12,7	8	1.1/16-12	0,37	9,5	1,26	32	1.1/4"	2,09	53,0	0,95	24,0
SP28251022	5/8	16	10	7/8-14	0,47	12,0	1,06	27	1.1/16"	2,68	68,0	0,95	24,0
SP28251027	5/8	16	10	1.1/16-12	0,47	12,0	1,26	32	1.1/4"	2,68	68,0	0,91	23,0
SP28251227	3/4	19	12	1.1/16-12	0,59	15,0	1,26	32	1.1/4"	2,72	69,0	1,06	27,0
SP28251230	3/4	19	12	1.3/16-12	0,59	15,0	1,42	36	1.7/16"	2,56	65,0	1,18	30,0
SP28251233	3/4	19	12	1.5/16-12	0,59	15,0	1,50	38	1.1/2"	2,84	72,0	1,18	30,0
SP28251633	1	25,4	16	1.5/16-12	0,79	20,0	1,50	38	1.1/2"	3,27	83,0	1,34	34,0

**JIC 90° FEMALE 37° FLARE WITH
CRIMPED NUT**

**FEMMINA JIC 90° SVASATURA 37° CON
DADO PINZATO**




DKJ-90

part nr. codice	hose ID			thread		d		hex E		cut-off C		drop H	
	[in]	[mm]	size	T	[in]	[mm]	[in]	[mm]	key	[in]	[mm]	[in]	[mm]
SP27250411	1/4	6,4	4	7/16-20	0,16	4,0	0,59	15	5/8"	0,99	25	0,95	24
SP27250412	1/4	6,4	4	1/2-20	0,16	4,0	0,67	17	11/16"	0,99	25	0,99	25
SP27250414	1/4	6,4	4	9/16-18	0,16	4,0	0,75	19	3/4"	1,06	27	1,02	26
SP27250514	5/16	8	5	9/16-18	0,22	5,5	0,75	19	3/4"	1,18	30	1,22	31
SP27250614	3/8	9,5	6	9/16-18	0,28	7,0	0,75	19	3/4"	1,30	33	1,26	32
SP27250619	3/8	9,5	6	3/4-16	0,28	7,0	0,95	24	15/16"	1,30	33	1,30	33
SP27250819	1/2	12,7	8	3/4-16	0,37	9,5	0,95	24	15/16"	1,54	39	1,50	38
SP27250822	1/2	12,7	8	7/8-14	0,37	9,5	1,06	27	1.1/16"	1,65	42	1,65	42
SP27250827	1/2	12,7	8	1.1/16-12	0,37	9,5	1,26	32	1.1/4"	1,54	39	1,65	42
SP27251022	5/8	16	10	7/8-14	0,47	12,0	1,06	27	1.1/16"	1,77	45	1,77	45
SP27251027	5/8	16	10	1.1/16-12	0,47	12,0	1,26	32	1.1/4"	1,77	45	1,77	45
SP27251227	3/4	19	12	1.1/16-12	0,59	15,0	1,26	32	1.1/4"	2,21	56	2,05	52
SP27251230	3/4	19	12	1.3/16-12	0,59	15,0	1,42	36	1.7/16"	2,21	56	2,09	53
SP27251233	3/4	19	12	1.5/16-12	0,59	15,0	1,50	38	1.1/2"	2,25	57	2,21	56
SP27251633	1	25,4	16	1.5/16-12	0,79	20,0	1,50	38	1.1/2"	2,76	70	2,56	65

**JIC 90° COMPACT FEMALE 74°
FLARE WITH CRIMPED NUT**

**FEMMINA JIC 90° COMPATTA SVASATURA
74° CON DADO PINZATO**



DKJ-90-K

part nr. codice	hose ID			thread		d		hex E		cut-off C		drop H	
	[in]	[mm]	size	T	[in]	[mm]	[in]	[mm]	key	[in]	[mm]	[in]	[mm]
SP41250411	1/4	6,4	4	7/16-20	0,16	4,0	0,55	14	9/16"	0,99	25	0,79	20
SP41250412	1/4	6,4	4	1/2-20	0,16	4,0	0,67	17	11/16"	0,99	25	0,83	21
SP41250414	1/4	6,4	4	9/16-18	0,16	4,0	0,75	19	3/4"	0,99	25	0,79	20
SP41250514	5/16	8	5	9/16-18	0,22	5,5	0,75	19	3/4"	1,02	26	0,95	24
SP41250614	3/8	9,5	6	9/16-18	0,28	7,0	0,75	19	3/4"	1,02	26	0,95	24
SP41250619	3/8	9,5	6	3/4-16	0,28	7,0	0,95	24	15/16"	1,02	26	0,91	23
SP41250819	1/2	12,7	8	3/4-16	0,37	9,5	0,95	24	15/16"	1,06	27	0,91	23
SP41250822	1/2	12,7	8	7/8-14	0,37	9,5	1,06	27	1.1/16"	1,06	27	0,91	23
SP41251022	5/8	16	10	7/8-14	0,47	12,0	1,06	27	1.1/16"	1,06	27	1,06	27
SP41251027	5/8	16	10	1.1/16-12	0,47	12,0	1,26	32	1.1/4"	1,06	27	1,14	29
SP41251227	3/4	19	12	1.1/16-12	0,59	15,0	1,26	32	1.1/4"	1,26	32	1,22	31
SP41251633	1	25,4	16	1.5/16-12	0,79	20,0	1,62	41	1.5/8"	1,38	35	1,46	37