


ORFS MALE

MASCHIO ORFS




AGO

part nr. codice	hose ID			thread		d		hex E		cut-off C	
	[in]	[mm]	size	T	[in]	[mm]	[in]	[mm]	key	[in]	[mm]
SP87250414	1/4	6,4	4	9/16-18	0,16	4,0	0,59	15	5/8"	0,91	23,2
SP87250517	5/16	7,9	5	11/16-16	0,22	5,5	0,75	19	3/4"	1,03	26,2
SP87250617	3/8	9,5	6	11/16-16	0,28	7,0	0,75	19	3/4"	1,03	26,2
SP87250621	3/8	9,5	6	13/16-16	0,28	7,0	0,87	22	7/8"	1,15	29,3
SP87250821	1/2	12,7	8	13/16-16	0,37	9,5	0,87	22	7/8"	1,15	29,3
SP87251025	5/8	15,9	10	1-14	0,47	12,0	1,06	27	1.1/16"	1,32	33,4
SP87251230	3/4	19	12	1.3/16-12	0,59	15,0	1,26	32	1.1/4"	1,41	35,9
SP87251634	1	25,4	16	1.7/16-12	0,79	20,0	1,50	38	1.1/2"	1,47	37,4

O-ring for male must be ordered separately
L'O-ring per il maschio deve essere ordinato separatamente.

ORFS FEMALE WITH HEXAGON AND CRIMPED NUT

FEMMINA ORFS CON ESAGONO E DADO PINZATO




ORFS

part nr. codice	hose ID			thread T	d		hex E			hex E1			cut-off C	
	[in]	[mm]	size		[in]	[mm]	[in]	[mm]	key	[in]	[mm]	key	[in]	[mm]
SP85000414	1/4	6,4	4	9/16-18	0,16	4,0	0,67	17	11/16"	0,55	14	9/16"	1,14	29
SP85000617	3/8	9,5	6	11/16-16	0,28	7,0	0,87	22	7/8"	0,75	19	3/4"	1,52	38,5
SP85000821	1/2	12,7	8	13/16-16	0,37	9,5	0,95	24	15/16"	0,87	22	7/8"	1,54	39
SP85001025	5/8	16	10	1-14	0,47	12,0	1,18	30	1.3/16"	0,95	24	15/16"	1,65	42
SP85001230	3/4	19	12	1.3/16-12	0,59	15,0	1,42	36	1.7/16"	1,18	30	1.3/16"	1,73	44
SP85001634	1	25,4	16	1.7/16-12	0,79	20,0	1,62	41	1.5/8"	1,42	36	1.7/16"	1,85	47

ORFS 45° FEMALE WITH CRIMPED NUT

FEMMINA ORFS 45° CON DADO PINZATO




ORFS-45

part nr. codice	hose ID			thread T	d		hex E			cut-off C		drop H	
	[in]	[mm]	size		[in]	[mm]	[in]	[mm]	key	[in]	[mm]	[in]	[mm]
SP85060414	1/4	6,4	4	9/16-18	0,16	4,0	0,67	17	11/16"	1,49	38,0	0,47	12,0
SP85060417	1/4	6,4	4	11/16-16	0,16	4,0	0,87	22	7/8"	1,57	40,0	0,55	14,0
SP85060617	3/8	9,5	6	11/16-16	0,28	7,0	0,87	22	7/8"	1,85	47,0	0,55	14,0
SP85060621	3/8	9,5	6	13/16-16	0,28	7,0	0,95	24	15/16"	1,85	47,0	0,63	16,0
SP85060821	1/2	12,7	8	13/16-16	0,37	9,5	0,95	24	15/16"	2,28	58,0	0,67	17,0
SP85060825	1/2	12,7	8	1-14	0,37	9,5	1,18	30	1.3/16"	2,36	60,0	0,67	17,0
SP85061025	5/8	16	10	1-14	0,47	12,0	1,18	30	1.3/16"	2,52	64,0	0,78	20,0
SP85061230	3/4	19	12	1.3/16-12	0,59	15,0	1,42	36	1.7/16"	3,11	79,0	0,86	22,0
SP85061634	1	25,4	16	1.7/16-12	0,79	20,0	1,62	41	1.5/8"	4,05	103,0	0,98	25,0

ORFS 90° FEMALE WITH CRIMPED NUT

FEMMINA ORFS 90° CON DADO PINZATO



ORFS-90

part nr. codice	hose ID			thread T	d		hex E			cut-off C		drop H	
	[in]	[mm]	size		[in]	[mm]	[in]	[mm]	key	[in]	[mm]	[in]	[mm]
SP85030414	1/4	6,4	4	9/16-18	0,16	4,0	0,67	17	11/16"	1,02	26	0,95	24
SP85030417	1/4	6,4	4	11/16-16	0,16	4,0	0,87	22	7/8"	1,02	26	1,02	26
SP85030617	3/8	9,5	6	11/16-16	0,28	7,0	0,87	22	7/8"	1,38	35	1,10	28
SP85030621	3/8	9,5	6	13/16-16	0,28	7,0	0,95	24	15/16"	1,34	34	1,22	31
SP85030821	1/2	12,7	8	13/16-16	0,37	9,5	0,95	24	15/16"	1,58	40	1,46	37
SP85030830	1/2	12,7	8	1.3/16-12	0,37	9,5	1,42	36	1.7/16"	1,65	42	1,46	37
SP85031025	5/8	16	10	1-14	0,47	12,0	1,18	30	1.3/16"	1,77	45	1,65	42
SP85031230	3/4	19	12	1.3/16-12	0,59	15,0	1,42	36	1.7/16"	2,25	57	1,85	47
SP85031634	1	25,4	16	1.7/16-12	0,79	20,0	1,62	41	1.5/8"	2,84	72	2,29	58