




SAE MALE 90° FLARE
MASCHIO SAE SVASATURA 90°


part nr. codice	hose ID			thread T	d		hex E			cut-off C	
	[in]	[mm]	size		[in]	[mm]	[in]	[mm]	key	[in]	[mm]
SP02580513	5/16	8	5	5/8-18	0,22	5,5	0,67	17	11/16"	1,14	29
SP02580613	3/8	9,5	6	5/8-18	0,28	7,0	0,67	17	11/16"	1,14	29
SP02581227	3/4	19	12	1.1/16-12	0,59	15,0	1,06	27	1.1/16"	1,54	39

**SAE FEMALE 90° FLARE WITH
CRIMPED NUT**
**FEMMINA SAE SVASATURA 90° CON DADO
PINZATO**



part nr. codice	hose ID			thread T	d		hex E			cut-off C	
	[in]	[mm]	size		[in]	[mm]	[in]	[mm]	key	[in]	[mm]
SP16290513	5/16	8	5	5/8-18	0,22	5,5	0,87	22	7/8"	0,59	15
SP16290613	3/8	9,5	6	5/8-18	0,28	7,0	0,87	22	7/8"	0,59	15
SP16291227	3/4	19	12	1.1/16-12	0,59	15,0	1,26	32	1.1/4"	0,75	19

**SAE 45° FEMALE 90° FLARE WITH
CRIMPED NUT**
**FEMMINA SAE 45° SVASATURA 90° CON
DADO PINZATO**


part nr. codice	hose ID			thread T	d		hex E			cut-off C		drop H	
	[in]	[mm]	size		[in]	[mm]	[in]	[mm]	key	[in]	[mm]	[in]	[mm]
SP28290513	5/16	8	5	5/8-18	0,22	5,5	0,87	22	7/8"	2,56	65	0,67	17
SP28290613	3/8	9,5	6	5/8-18	0,28	7,0	0,87	22	7/8"	1,65	42	0,67	17
SP28290613L	3/8	9,5	6	5/8-18	0,28	7,0	0,87	22	7/8"	1,97	50	0,71	18

**SAE 90° FEMALE 90° FLARE WITH
CRIMPED NUT**


**FEMMINA SAE 90° SVASATURA 90° CON
DADO PINZATO**



part nr. codice	hose ID			thread T	d		hex E			cut-off C		drop H	
	[in]	[mm]	size		[in]	[mm]	[in]	[mm]	key	[in]	[mm]	[in]	[mm]
SP27290513	5/16	8	5	5/8-18	0,22	5,5	0,87	22	7/8"	1,14	29	1,22	31
SP27290613	3/8	9,5	6	5/8-18	0,28	7,0	0,87	22	7/8"	1,30	33	1,26	32

SAE SWIVEL MALE INVERTED FLARE


MASCHIO SAE GIREVOLE CONO INVERSO



part nr. codice	hose ID			thread T	hex E			cut-off C	
	[in]	[mm]	size		[in]	[mm]	key	[in]	[mm]
SP80000411	1/4	6,4	4	7/16-24	0,47	12	1/2"	1,50	38
SP80000412	1/4	6,4	4	1/2-20	0,55	14	9/16"	2,17	55
SP80000612	3/8	9,5	6	1/2-20	0,55	14	9/16"	2,21	56
SP80000613	3/8	9,5	6	5/8-18	0,67	17	11/16"	2,25	57
SP80000819	1/2	12,7	8	3/4-18	0,75	19	3/4"	2,36	60

**SAE 45° SWIVEL MALE INVERTED
FLARE**


MASCHIO SAE 45° GIREVOLE CONO INVERSO



part nr. codice	hose ID			thread T	hex E			cut-off C		drop H	
	[in]	[mm]	size		[in]	[mm]	key	[in]	[mm]	[in]	[mm]
SP80060612	3/8	9,5	6	1/2-20	0,55	14	9/16"	1,89	48	0,99	25
SP80060613	3/8	9,5	6	5/8-18	0,67	17	11/16"	2,13	54	1,18	30

SAE 90° SWIVEL MALE INVERTED
FLARE

MASCHIO SAE 90° GIREVOLE CONO INVERSO



part nr. codice	hose ID			thread T	hex E			cut-off C		drop H	
	[in]	[mm]	size		[in]	[mm]	key	[in]	[mm]	[in]	[mm]
SP80030411	1/4	6,4	4	7/16-24	0,47	12	1/2"	1,14	29	1,42	36
SP80030412	1/4	6,4	4	1/2-20	0,55	14	9/16"	1,18	30	1,34	34
SP80030612	3/8	9,5	6	1/2-20	0,55	14	9/16"	1,18	30	1,38	35
SP80030613	3/8	9,5	6	5/8-18	0,67	17	11/16"	1,22	31	1,73	44
SP80030819	1/2	12,7	8	3/4-18	0,75	19	3/4"	1,38	35	1,77	45