



1 W/B



2 W/B



4 W/S



6 W/S

ISO 18752 STANDARD EXCEED SERIES
 Inner Tube : Oil resistance synthetic rubber
 Reinforcement : High-tensile steel wire
 Cover : Abrasion and weather resistant synthetic rubber
 Working Temperature : -40°C +120 (S/W)
 -40°C+100 (W/B)

ISO 18752 STANDARD SERIE EXCEED
 Sottostrato : gomma sintetica resistente all'olio.
 Rinforzo : treccia d'acciaio
 Copertura : gomma sintetica resistente all'ozono e agenti atmosferici
 Temperatura di Esercizio : -40°C / +120°C (S/W) -40°C+100 (W/B)

ISO 21

part nr. codice	ID			OD		Reinforcement Rinforzi	WP		BP		MBR		TW	
	[in]	[mm]	size	[in]	[mm]		[psi]	[bar]	[psi]	[bar]	[in]	[mm]	[lb/ft]	[Kg/mt]
01Y2100104	1/4"	6,3	04	0,49	12,4	1W/B	2972	205	11890	820	1,77	45	0,121	0,18
01Y2100206	3/8"	9,5	06	0,66	16,7	2W/B	2972	205	11890	820	2,36	60	0,241	0,36
01Y2100208	1/2"	12,7	08	0,80	20,4	2W/B	2972	205	11890	820	3,14	80	0,328	0,49
01Y2100210	5/8"	15,9	10	0,95	24,1	2W/B	2972	205	11890	820	4,33	110	0,429	0,64
01Y2100212	3/4"	19	12	1,13	28,7	2W/B	2972	205	11890	820	5,11	130	0,623	0,93
01Y2100416	1"	25,4	16	1,41	35,9	2W/B	2972	205	11890	820	7,08	180	0,925	1,38
01Y2100420	1.1/4"	31,8	20	1,74	44,3	4S/W	2972	205	11890	820	11,02	280	1,327	1,98
01Y2100424	1.1/2"	38,1	24	2,06	52,3	4S/W	2972	205	11890	820	13,38	340	2,023	3,02
01Y2100432	2"	50,1	32	2,60	66	4S/W	2972	205	11890	820	14,96	380	3,116	4,65

ISO 28

part nr. codice	ID			OD		Reinforcement Rinforzo	WP		BP		MBR		TW	
	[in]	[mm]	size	[in]	[mm]		[psi]	[bar]	[psi]	[bar]	[in]	[mm]	[lb/ft]	[Kg/mt]
01Y2800204	1/4"	6,3	04	0,53	13,5	2W/B	3987	275	15950	1100	1,77	45	0,188	0,28
01Y2800206	3/8"	9,5	06	0,66	16,7	2W/B	3987	275	15950	1100	0,34	60	0,248	0,37
01Y2800208	1/2"	12,7	08	0,83	21,2	2W/B	3987	275	15950	1100	3,15	80	0,342	0,51
01Y2800410	5/8"	16,0	10	1,04	26,5	4S/W	3987	275	15950	1100	6,30	160	0,670	1
01Y2800412	3/4"	19,0	12	1,16	29,5	4S/W	3987	275	15950	1100	6,70	170	0,771	1,15
01Y2800416	1"	25,4	16	1,46	37	4S/W	3987	275	15950	1100	8,66	220	1,126	1,68
01Y2800420	1.1/4"	31,8	20	1,79	45,4	4S/W	3987	275	15950	1100	11,0	280	1,668	2,49
01Y2800424	1.1/2"	38,1	24	2,06	52,3	4S/W	3987	275	15950	1100	13,4	340	2,023	3,02
01Y2800432	2	50,8	32	2,60	66	4S/W	3987	275	15950	1100	15,0	380	3,116	4,65

ISO 35

part nr. codice	ID			OD		Reinforcement Rinforzo	WP		BP		MBR		TW	
	[in]	[mm]	size	[in]	[mm]		[psi]	[bar]	[psi]	[bar]	[in]	[mm]	[lb/ft]	[Kg/mt]
01Y3500408	1/2"	12,7	08	0,91	23,1	4S/W	5002	345	20010	1380	5,51	140	0,576	0,86
01Y3500410	5/8"	16,0	10	1,04	26,5	4S/W	5002	345	20010	1380	6,30	160	0,670	1
01Y3500412	3/4"	19,0	12	1,20	30,4	4S/W	5002	345	20010	1380	7,48	190	0,898	1,34
01Y3500416	1"	25,4	16	1,48	37,5	4S/W	5002	345	20010	1380	9,45	240	1,293	1,93
01Y3500620	1.1/4"	31,8	20	1,90	48,4	6S/W	5002	345	20010	1380	14,5	370	2,459	3,67
01Y3500624	1.1/2"	38,1	24	2,20	56	6S/W	5002	345	20010	1380	18,5	470	2,814	4,2
01Y3500632	2	50,8	32	2,80	71,1	6S/W	5002	345	20010	1380	19,7	500	4,824	7,2