



**BRAIDED FLEXIBLE HOSE**

Inner Tube : nitril rubber  
 Cover : galvanized steel braiding AISI 1008  
 braid  
 Working Temperature : -10°C / +70°C

**TUBO FLESSIBILE CALZATO**

Sottostrato : gomma nitrilica  
 Copertura : calza in acciaio zincato AISI 1008  
 Temperatura di Esercizio : -10°C / +70°C

**PRO BR**

part nr. codice	ID			OD		WP		BP		MBR	
	[in]	[mm]	size	[in]	[mm]	[psi]	[bar]	[psi]	[bar]	[in]	[mm]
0114431503	3/16"		03	0,39	10,0	218	15	1088	75	2,76	70,0
0114431504	1/4"		04	0,43	11,0	218	15	1088	75	1,18	30,0
0114431505	5/16"		05	0,51	13,0	218	15	1088	75	1,58	40,0
0114431506	3/8"		06	0,59	15,0	218	15	1088	75	1,77	45,0
0114431508	1/2"		08	0,75	19,0	218	15	870	60	1,97	50,0
0114431510	5/8"		10	0,87	22,0	145	10	870	60	2,76	70,0
0114431512	3/4"		12	0,99	25,0	145	10	725	50	3,15	80,0
0114431516	1"		16	1,26	32,0	145	10	653	45	3,94	100,0

Thanks to our machines we have the possibility to braid up to 1SN 1" or 2SC 1" with galvanized steel or AISI 316L braid, minimum q.ty 100mt.  
 Grazie alle nostre macchine abbiamo la possibilità di trecciare fino a 1SN 1" o equivalente 2SC 1", in acciaio zincato e in acciaio inox AISI 316L per q.tà superiori ai 100mt.

